

**Silencer**  
**AMTE-M-LH-G14**  
Part number: 1205861

**FESTO**



**Data sheet**

| Feature                            | Value                                                              |
|------------------------------------|--------------------------------------------------------------------|
| Mounting position                  | optional                                                           |
| Size of pack                       | 20                                                                 |
| Operating pressure                 | 0 MPa...1 MPa<br>0 bar...10 bar                                    |
| Flow rate to atmosphere            | 3140 l/min                                                         |
| Explosion protection               | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Operating medium                   | Compressed air to ISO 8573-1:2010 [7:-:-]                          |
| Note on operating and pilot medium | Lubricated operation possible                                      |
| Corrosion resistance class CRC     | 1 - Low corrosion stress                                           |
| LABS (PWIS) conformity             | VDMA24364-B1/B2-L                                                  |
| Sound pressure level               | 83 dB(A)                                                           |
| Ambient temperature                | -40 °C...80 °C                                                     |
| Product weight                     | 13 g                                                               |
| Pneumatic connection               | G1/4                                                               |
| Material shock absorber insert     | Bronze                                                             |
| Material screwed plug              | Brass                                                              |
| Note on materials                  | RoHS-compliant                                                     |